



TECHNICAL DATA SHEET

POINTPAK PVC SHEET (Class 1)

Thickness	350 micron		
Breaking load	Longitudinally Orizzontal	32 - 37 N/mm ² 27 - 32 N/mm ²	DIN 53 455 DIN 53 455
Tensile Strength	Longitudinally Orizzontal	min. 42 - 47 N/mm ² min. 37 - 43 N/mm ²	DIN 53 455 DIN 53 455
Breaking Elongation	Longitudinally Orizzontal	150 - 200 % 100 - 150 %	
Tensile value	Longitudinally Orizzontal	2,5 - 3 % 0,0 - 0,5 %	
Softening Point		86 +/- 1 ° C	DIN 53 460
Density		1,38 g/ccm +/- 0,01	
Auto Wrapping		85 mm +/- 10 % (measured halfway through the 25ml roll)	
Response to fire		B2 (Class 1)	DIN 4102
Standard Size	1.000 mm x 25.000 mm		
Special size	1.200 mm x 25.000 mm		

- * All our products are the result of in-depth research and correspond to the best of technological development.
- * We provide you with data and indications for the appropriate use of the products without any guarantee.
- * We recommend that you perform specific tests to verify which of our products to use for specific uses.
- * Technical data are indicative. We reserve the right to make any technical changes.

POINTWOOL YALITIM DIS TICARET LIMITED SİRKETİ

İSTANBUL / KAYSERİ / TÜRKİYE

WhatsApp : +90 542 385 6074